

Graphite electrode

RP, HP, SHP dan UHP berdasarkan grade, diameter, panjang, nipple, aplikasi dan tujuan.

Product specification sheet

Overview

RFQ electrode perlu grade, diameter, panjang, nipple, kondisi furnace, jumlah dan tujuan.

Key specifications

Ringkasan	Graphite electrode
Spesifikasi kunci	Karbon tetap, belerang, abu, kelembapan, zat volatil, ukuran partikel
Field RFQ	Nama produk, target spesifikasi, jumlah, kemasan, tujuan and contact details.

Applications

- RFQ material carbon
- Spesifikasi kunci
- Minta Penawaran

RFQ checklist

Nama produk
Grade
Diameter
Length
Nipple
Furnace condition
Jumlah
Packing
Estimasi delivery
Dokumen yang dibutuhkan

Specification notes and batch confirmation

Technical purchasing fields

- Specifications: Karbon tetap, belerang, abu, kelembapan, zat volatil, ukuran partikel or dimensions
- Typical carbon material ranges: CPC ukuran 0-1 mm / 1-5 mm / 0-2 mm / 0-8 mm / 8-30 mm / 0-5 mm; GPC ukuran 0-5 mm / 1-5 mm / 0-10 mm; petroleum coke belerang 2-5%, abu <0.5%, VM 8-12%, kelembapan 8-9%
- Batch rule: Typical ranges are for RFQ preparation; final specification is subject to available batch COA
- Order data: Quantity, kemasan, tujuan, aplikasi and expected delivery time
- Documents: COA, photos, kemasan details and batch data when needed

RFQ preparation

For Graphite electrode, send product name, target spesifikasi, jumlah, kemasan, tujuan and aplikasi before requesting price.